

Connolly News



September
Quarter
2002
Late Edition

A publication by Connolly KEY JOINT Pty. Ltd.

If your contact details have changed please phone Connolly toll free on 1800 335 215 or use the fax back form below

New Dowel Sleeves Released

Connolly has just released their new range of full length dowel sleeves onto the market. The new Universal Dowel Sleeve (UDS) allows a variety of joint types to be constructed using the one type of sleeve.

The Connolly UDS is suitable for uses with Connolly key joint as a doweled key joint, as a face fixed sleeve to timber or steel formwork, as part of a pre assembled dowel basket or as a clip on dowel for use with support bars ("train tracks").

It comes in sizes to suit 16mm and 20mm dowels in both round and square configurations. The standard length is 300mm but this can be altered on site or supplied shorter by request.

Unlike many square dowel sleeves the Connolly square UDS has unique end closers to prevent slurry entering the sleeve at the sides of the dowels. This ensures the dowel is free to move laterally within the sleeve as required.

The Connolly round UDS is supplied with a face fixing plug and nails for fixing to timber formwork. This makes it the fastest sleeve on the market to fix in place.

These are only some of the many features of the new Connolly dowel sleeves. If you would like further information or a free sample fill in the details below and fax back to the number shown.

Customer Service

Paul Mroz has joined the team at Connolly in the role of Customer Service. Paul has a strong background in customer service within the finance industry. Since joining the Connolly team in September he has undergone extensive training on the full range of Connolly products, their applications and correct methods of installation.

Paul will be based at our Casino manufacturing facility but will be spending a large proportion of his time on the road or in the air. For information or assistance he can be contacted on 0421 599 507.

Joint Location

The location of contraction joints is an important part of overall slab performance and should be considered early in the design stage. The slab sections or panels should have a length to width ratio of a maximum of 1.5:1 and preferably 1:1. Panel shapes such as "L" and "T" should be avoided where possible.

New Zealand Distributor Appointed

We have recently appointed a new distributor based in Christchurch. Although Connolly's range of products have been available in New Zealand for a number of years, CANZAC Construction Products is set to take the presence of Connolly in New Zealand to new heights. They are a specialist supplier of Concrete accessories with a strong presence in both the North and South Islands. Lance and his trusty team of experienced staff are always willing to share the knowledge that they have acquired over many years in the construction industry. For New Zealand enquiries they can be contacted directly on 03 3434 254.

Please provide details below and Fax back to 02 6662 3263 for more information on any items of interest.

Please send me more information on

.....
.....



" the key to a better job "

Tick this box if you do not wish to receive future newsletters

Name:.....
Address:.....
.....
Phone:.....
Fax:.....
E-mail:.....